

ACTIVE REMOTE SYSTEMS LLC
TECHNOCRANE & SUPERTECHNO CRANE
SPEC SHEET

FEATURES	TECHNOCRANE		SUPERTECHNO	
	15'	21'	30'	50'
ARM				
OVERALL LENGTH - CLOSED	8' 10"	14' 4"	16'	23' 2"
OVERALL LENGTH - OPEN	19' 1"	27' 6"	37' 8"	60' 7"
FULCRUM TO FRONT END - CLOSED	3' 4"	7' 9"	8' 4"	11'
FULCRUM TO FRONT END - OPEN	13' 7"	21'	30'	48' 5"
TAIL TO FULCRUM	5' 6"	6' 6"	7' 8"	12' 2"
MAXIMUM LENS HEIGHT	15' 3"	21'	30'	50'
WEIGHT (ARM ONLY)	287 lbs.	396 lbs.	550 lbs.	1628
APPROXIMATE "ALL UP" WEIGHT	1153 lbs.	1870 lbs.	3000 lbs.	5622 lbs.
DOLLY				
LENGTH	3' 7"	5' 5"	5'	8'
WIDTH	2' 6"	3' 7"	4' 6"	6' 5"
WIDTH W/ WHEELS OFF	?	2' 9"	3' .5"	
POST HEIGHT (ground to bottom of pan pivot)		3' 10"	3' 9.5"	
HIGHEST POSITION ("TALL POST")	6' 10"	7' 11"	7' 3.5"	10'
LOWEST POSITION ("SHORT POST")	5' 9"	6' 6"	5' 11"	6' 10"
TRACK WIDTH	2' 11"	24.5"	1 Meter Wide=39.3701"	
TELE TRAVEL FULL EXTEND & RETRACT		2.5 Seconds		
FEET / SECOND TRAVEL	.75 M/S	5.25 FPS		6.6 FPS
WEIGHT	148 lbs.			1267 lbs.
COLUMN	68 lbs.			906 lbs.
MAXIMUM TILT	60 degrees	53 degrees	53 Degrees	
REMOTE HEAD				
REMOTE HEAD TYPE	Z Head	Power Pod Plus	Power Pod 2000	Z Head
LENGTH IN SHORTEST CONFIGURATION	2' 2"		25"	2' 2"
LENGTH IN TALLEST CONFIGURATION	3' 3"		37.5"	3' 3"
WIDTH	15"-18"	17.5"	24"	15"-18"
DEPTH			11.75"	
WEIGHT	59 lbs.	63 lbs.	70 lbs.	70 lbs.
PAN & TILT MOVEMENT	3 revolutions	Unlimited	Unlimited	3 revolutions
MAXIMUM SPEED			3 Seconds/360 Degrees	
DIGITAL MOTION CAPTURE CAPABLE?	No	No	Yes	No